

WHAT IS CLAIMED IS:

1. An image processing apparatus comprising:

a block expanding section formed in a semiconductor chip, which handles an area to be drawn
5 in units of blocks each composed of a plurality of pixels, and performs expansion calculation of information on a representative point of each block;
and

a plurality of pixel processing sections formed in
10 the semiconductor chip, each of said plurality of pixel processing sections comprises: a pixel expanding section which receives block representative point information calculated in the block expanding section and expands information in units of pixels at least in
15 a rectangular area from the information; and a computing section which receives information expanded by the pixel expanding section and performs computation in units of pixels from the information, each of said plurality of pixel processing sections performs
20 graphics processing in cooperation with the block expanding section, and performs image processing independent of the block expanding section.

2. The image processing apparatus according to claim 1, wherein the pixel expanding section comprises:

25 a loop counter section which controls counting of a multiple loop;
a buffer;

a buffer address calculating section connected to the loop counter section and the buffer, which calculates an address for reading data from the buffer; and

5 an address and parameter calculating section connected to the buffer, which reads data from the buffer and calculates a plurality of parameters and memory addresses required for the computing section.

3. The image processing apparatus according to
10 claim 1, wherein the computing section comprises:

 a plurality of product sum calculating sections which perform computation using data read from a memory inside or outside the image processing apparatus in accordance with a plurality of addresses calculated by
15 the pixel expanding sections and a plurality of parameters calculated by the pixel expanding section; and

 an accumulator added at the final stage of the product sum calculating sections, which performs
20 accumulation instead of data reading from the memory.

4. The image processing apparatus according to claim 3, wherein each of said plurality of pixel processing sections further comprises a First-in First-out buffer circuit which is connected to the computing
25 section and from/into which data is written into/read from the computing section.

5. The image processing apparatus according to

claim 3, wherein each of said plurality of pixel
processing sections further comprises a buffer circuit
which is connected to the pixel expanding section and
the computing section, into which data is written from
5 the computing section, and from which data is read into
the pixel expanding section.

6. The image processing apparatus according to
claim 3, wherein each of said plurality of pixel
processing sections further comprises a buffer circuit
10 which is connected to the pixel expanding section and
the computing section, and which has a first pass into
which data is written from the computing section and
from which data is read into the pixel expanding
section and a second pass from which data is read into
15 the computing section in accordance with an address
from the pixel expanding section.

7. An image processing apparatus comprising:
a plurality of image processing sections, each of
said plurality of image processing sections comprises:
20 a block expanding section formed in a
semiconductor chip, which handles an area to be drawn
in units of blocks each composed of a plurality of
pixels, and performs expansion calculation of
information on a representative point of each block;
25 and

a plurality of pixel processing sections formed in
the semiconductor chip, each of said plurality of pixel

processing sections includes: a pixel expanding section
which receives block representative point information
calculated in the block expanding section and
expands information in units of pixels at least in
5 a rectangular area from the information; and
a computing section which receives information expanded
by the pixel expanding section and performs computation
in units of pixels from the information, each of said
plurality of pixel processing sections performs
10 graphics processing in cooperation with the block
expanding section, and performs image processing
independent of the block expanding section, and each
of said plurality of image processing sections
simultaneously performs processings different from each
15 other.

8. An image processing apparatus comprising:
a pixel expanding section formed in
a semiconductor chip, which handles an area to be drawn
in units of blocks each composed of a plurality of
20 pixels and calculates a representative value of each
pixel in each block; and

a plurality of pixel processing sections formed in
the semiconductor chip, each of said plurality of pixel
processing sections comprises: an address calculating
25 section which receives a pixel representative value
calculated in the pixel expanding section and
calculates a parameter and an address of a pixel at

least in a rectangular area; and a computing section which receives an address calculated in the address calculating section and performs partial computation of pixel processing using data read from a memory

5 according to the address, each of said plurality of pixel processing sections performs graphics processing in cooperation with the pixel expanding section, and performs image processing independent of the pixel expanding section.

10 9. The image processing apparatus according to claim 8, wherein each of said plurality of pixel processing sections further comprises a First-in First-out buffer circuit which is connected to the computing section and from/into which data is written
15 into/read from the computing section.

10. The image processing apparatus according to claim 8, wherein each of said plurality of pixel processing sections further comprises a buffer circuit which is connected to the pixel expanding section and
20 the computing section, into which data is written from the computing section, and from which data is read into the pixel expanding section.

11. The image processing apparatus according to claim 8, wherein each of said plurality of pixel
25 processing sections further comprises a buffer circuit which is connected to the pixel expanding section and the computing section and which has a first pass into

which data is written from the computing section and
from which data is read into the pixel expanding
section and a second pass from which data is read into
the computing section according to an address from the
5 pixel expanding section.

12. An image processing apparatus comprising:

a plurality of image processing sections, each of
said plurality of image processing sections comprises:

a pixel expanding section formed in a
10 semiconductor chip, which handles an area to be drawn
in units of blocks each composed of a plurality of
pixels and calculates a representative value of each
pixel in each block; and

a plurality of pixel processing sections formed in
15 the semiconductor chip, each of said plurality of pixel
processing sections includes: an address calculating
section which receives a pixel representative value
calculated in the pixel expanding section and
calculates a parameter and an address of a pixel at
20 least in a rectangular area; and a computing section
which receives an address calculated in the address
calculating section and performs partial computation of
pixel processing using data read from a memory
according to the address, each of said plurality of
25 pixel processing sections performs graphics processing
in cooperation with the pixel expanding section, and
performs image processing independent of the pixel

expanding section, and each of said plurality of image processing sections simultaneously performs processings different from each other.